

Important Safeguards and Warnings



- Please read this manual carefully before using the product.
- The use must conform to local electrical safety regulations.
- The size of the DC interface on the product output cable should match the size of the terminal product interface.
- Before powering on, make sure that the powering voltage conforms to the product input voltage.
- When connecting the product with the terminal product, do not operate with power. During wiring, the input and output specifications and parameters need to meet the product requirements.
- To reduce the risk of fire or electric shock, do not expose the product to rain or moisture.
- If the product does not work properly, contact the store where you purchased the product or the nearest service center. Do not disassemble or dismantle the device without a professional present. (The company is not responsible for damages to the device or other product problems caused by excessive use or other improper use).

DH-PFM320-020EN

User's Manual

1 Features

CCTV Power supply, 100-240 VAC to 12 VDC 2 A; Wall plug, easy to use. Overvoltage, overcurrent, and short circuit protection. Good quality, stable performance, V0 level flame resistance.

2 Key Parameters

Input voltage: 100 VAC—240 VAC, 50/60Hz
Output voltage: 12 VDC
Output current: 2 A
No-Load power consumption: ≤ 0.1 W
Working temperature: 0 °C to 40 °C (32 °F to 104 °F)
Transformation Efficiency: $\geq 86.20\%$

3 Appearance

- Dimensions: 70.0mm×40.0mm×27.5mm (2.76" × 1.57" × 1.08")
- Input: Plug with European standard
- Output: $\Phi 5.5$ mm× $\Phi 2.1$ mm×10 mm ($\Phi 0.22$ " × $\Phi 0.08$ " × 0.39")

4 Installation Dimensions

mm [inch]

