


Product Comparison

Technical Parameters	 Selected Product  COMPARE  COMPARE Add product to compare		
	DS-PK670MDWNP/Black Touchscreen Keypad Black	DS-PK670MDW-HWE/White Touchscreen Keypad White	DS-PK670W/White Touchscreen Keypad White
Max. Zones	2	2	N.A.
On-Board Zones	2	2	N.A.
Max. Outputs	1	1	N.A.
Event Log Records	200	200	200
Display	7" Colorful LCD with resolution 600*1024	7" Colorful LCD with resolution 600*1024	7" Colorful LCD with resolution 600*1024
Indication	1 indicator(Yellow\Green\Red)	1 indicator(Yellow\Green\Red)	1 indicator(Yellow\Green\Red)
Key Button	1	1	1
Tag	Supported M1/DESFire® Card	Supported M1/DESFire® Card	N.A.
PIN	4~6 digits	4~6 digits	4~6 digits
Bus-Extender	x	x	N.A.
Bus Technology	Half-Duplex RS-485	Half-Duplex RS-485	Half-Duplex RS-485
Bus Wiring	4-Core Alarm Cable (at least 2x0.5mm2+2x0.22mm2)	4-Core Alarm Cable (at least 2x0.5mm2+2x0.22mm2)	4-Core Alarm Cable (at least 2x0.5mm2+2x0.22mm2)
LAN/Ethernet	Supported,10/100 Mbps self-adaptive	Supported,10/100 Mbps self-adaptive	Supported,10/100 Mbps self-adaptive
Wi-Fi	Supported,802.11b/g/n (2.4GHz)	Supported,802.11b/g/n (2.4GHz)	Supported,802.11b/g/n (2.4GHz)
Quiescent Current	270mA@12VDC	270mA@12VDC	270mA@12VDC
Input Voltage	12 VDC nominal (9~24 VDC),powered by bus	12 VDC nominal (9~24 VDC),powered by bus	12 VDC nominal (9~24 VDC),powered by bus
Max. Current	400mA@12VDC	400mA@12VDC	400mA@12VDC
Relay Output	1,1A 30VDC	1,1A 30VDC	NA
Operating Temperature	-10°C to 50°C	-10°C to 50°C	-10°C to 50°C
Storage Temperature	-10°C to 50°C	-10°C to 50°C	-10°C to 50°C
Relative Humidity	10%-90% non-condensing	10%-90% non-condensing	10%-90% non-condensing
Dimension (W × H × D)	122mmx218.7mmx27mm	122mmx218.7mmx27mm	122mmx218.7mmx27mm
Weight	400g	400g	400g
Installation Method	Wall mounting	Wall mounting	Wall mounting
Tamper-Proof	Front and Rear	Front and Rear	Front and Rear
Electrical Conformity	CE,CB	CE,CB	CE,CB
EN 50131	Security Grade 2,Enconmental Class II	Security Grade 2,Enconmental Class II	Security Grade 2,Enconmental Class II
LED Indication	Supported	Supported	Supported
SD Card	FAT32, up to 128G For storing alarm verification videos or pictures	FAT32, up to 128G For storing alarm verification videos or pictures	FAT32,up to 128G For storing alarm verification videos or pictures
Loudspeaker	Supported	Supported	Supported
Mic	Reserved	Reserved	Reserved

Debug Port	2	2	2
POE	IEEE 802.3af	N.A.	N.A.
Application Scenario	Indoor	Indoor	Indoor
Shell Material	Plastic	Plastic	Plastic
Color	White or Black	White or Black	White or Black