


CODE: **R812T** v.1.0/1

TYPE: **R 12V/8x1,5A/TOPIC RACK** mounted power supply for up to 8 analog cameras.



Features:

- DC 12V/8x1A uninterruptible power supply for powering analog cameras ($\Sigma I = 8A$ max.)
- the adjustment of output voltage in the range 12V÷15V DC available from the front panel of the power supply unit
- 8 outputs independently protected by 1,5A melting fuses
- wide range of mains supply AC: 176÷264V AC
- high efficiency 83%
- LED optical indication: AC, DC, TEMP, LoB, ALARM, AUX1 ÷ AUX8
- acoustic indication of failure
- control of voltage presence at the AUX1 ÷ AUX8 outputs
- the ALARM technical output of collective failure –relay type, activated by:
 - 230V AC power loss
 - activation of the output fuse in the camera power supply circuit
 - too high temperature of the PSU (>70°C)
 - the PSU failure
- protections:
 - SCP short-circuit protection
 - OVP overvoltage protection
 - overvoltage protection
 - overload protection OLP
- forced cooling (fan)
- warranty – 2 year from the production date

DESCRIPTION

The **R812T** power supply unit is designed for uninterrupted power supply of up to 8 analog cameras requiring stabilized voltage of **12V DC** with the total current efficiency of **8A**. The output voltage adjustment range is adjusted via a potentiometer within the range of **12V÷15V DC**. The PSU is fitted with 8 outputs protected independently with melting fuse 1,5A. The power supply is fitted with the **ALARM** output of collective failure. In case of failure, relay contacts are switched automatically, which is accompanied by acoustic and optical indication (the corresponding led goes on). The power supply construction is based on the switch mode PSU with high energy efficiency and is located in an enclosure adapted for mounting in standard **RACK 19"** cabinets.

RACK POWER series power supply unit

RACK mounted power supply 12V DC for up to 8 analog cameras



SPECIFICATIONS	
PSU type:	A (EPS - External Power Source)
Mains supply:	176÷264V AC 50÷60Hz
Current up to:	0,9A@230V AC max.
Supply power:	96W max.
Efficiency:	83%
Output voltage:	12V DC
Voltage adjustment range output	12÷15V DC
Output current	8 x 1A ($\Sigma I = 8A$) max. @12V
Ripple:	100 mV p-p max.
Short-circuit protection SCP	8 x F 1,5A melting fuse
Overload protection OLP	105% ÷ 150% of the PSU power, automatic return
Surge protection	varistors
Overvoltage protection OVP	>16V (automatic recovery)
The ALARM technical output of collective failure	Relay type: 1A@ 30VDC/50VAC
Optical indication of operation:	LED: AC, DC, TEMP, ALARM, AUX1÷AUX18
Acoustic operation indication:	Piezoelectric indicator ~75dB/0,3m
Operating conditions:	2nd environmental class, -10 °C÷45 °C
Enclosure:	Steel plate RAL 9005, black
Enclosure dimensions:	W=19", H=2U; 482 x 88 x 223 mm (WxHxD)
Net weight:	5,30kg / 5,70kg
Fixation	four-point butt mounting to RACK profiles – the set include 4 M6 screws + cage nuts
Declarations, warranty	CE, 2 year from the production date
Notes:	Forced cooling (fan). 230V AC input: the IEC C14 socket with a fuse, power cable 1,5m (included) Outputs: ALARM, AUX1÷AUX8: $\Phi 0,5-2,1$ (AWG 24-12) 0,5-2mm ²